


IRIS®




P3MR P3MRREMOTE

3" IC PLATFORM

Low Voltage MR16



- IC rated platform which utilizes halogen MR16 lamps to deliver powerful beams of light from a diminutive 3.5" aperture.
- Platform accepts Optical Elements for downlighting, accent lighting, wall washing and shower lighting applications.
- Optical elements can be changed after installation to adapt the fixture to changing lighting needs as artwork, furniture or other home features are changed.



Ceiling Cutout
4 3/8" (112mm)

DESCRIPTION

A specification grade residential platform dedicated for low voltage MR16 lamps featuring a TruVolt™ toroidal transformer with secondary outputs for either switch or dimmer controlled applications. Platform is airtight and may be used in direct contact with insulation.

Complete fixture requires an IRiS optical element

Features

- Optical matte black powder coat inside platforms for a visually dark interior
- Integral thermal protector
- 1/2" plaster lip with centerline notches for precise drywall holes or for use with wet plaster
- No flex bar hangers have a tab for consistent depth and set screws to lock the horizontal placement. Bars span 22 1/2" for 24" joist construction
- Platforms are shipped with overspray protector installed in aperture
- Platform is air tight to prevent dust marks on ceilings, prevent room drafts and prevent energy loss

- Soft focus lens standard for smooth beam patterns
- Platform is wet location listed when used with shower elements
- 5 year warranty on transformer

Listings

- CUL and UL Listed for Damp Location
- CUL and UL listed for Feed Through
- CUL and UL listed for Direct Contact with Insulation and combustible material
- Meets State of California Title 24
- Meets Washington State Energy Code
- Meets International Energy Conservation Code (IECC)
- Meets New York State Energy Conservation Construction Code (NY-ECCC)
- Certified Under ASTM-E283

